

# Bảng thông số sản phẩm

Thông số kỹ thuật



## APC Easy UPS BVX 700VA, 230V, AVR, USB Charging, Universal Sockets

BVX700LUI-MS

### Overview

Lead time Usually in Stock

### Main

Input voltage 230 V AC 1 phase

Output voltage 230 V AC 1 phase

Rated power in W 360 W

Rated power in VA 700 VA

Plug standard IEC 60320 C14

Nb of power socket outlets 2 universal

Cable length 1.22 m

Number of cables 1

Battery type Lead-acid battery

Provided equipment User manual

### General

Max runtime 120 min

Number of power module free slots 0

Number of power module filled slots 0

Redundant No

UPS size WS

### Physical

Colour Black

Height 13.8 cm

Width 9.8 cm

Depth 31 cm

Net weight 4.2 kg

Mounting support Floor

Mounting preference No preference

Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No

## Input

Network frequency	50/60 Hz +/- 5 Hz auto-sensing
Input voltage limits	170...280 V 230 V AC
Cos phi	0.51

## Output

Maximum configurable power in W	360 W
Output frequency	50/60 Hz +/- 1 Hz sync to mains
UPS type	Line interactive
Wave type	Stepped approximation to a sinewave
Full load runtime	00:00:01 360 W
Graph display	1
Half load runtime	00:06:00 180 W
Maximum configurable power in VA	700 VA
Transfer time	6 ms typical : 10 ms maximum

## Conformance

Product certifications	CE CB
Equipment protection policy	Lifetime : 50000 euros

## Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...3000 m
Ambient air temperature for storage	-15...40 °C
Storage Relative Humidity	Non-condensing 0...95 %
Storage altitude	0...3000 m
Acoustic level	40 dBA
IP degree of protection	IP20

## Batteries & Runtime

Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	8 h
Battery voltage	12 V
Battery capacity	7.0 Ah
Battery life	2...3 year(s)
Replacement battery	<a href="#">APCRBC110</a> 

---

Extended runtime	0
------------------	---

---

## Communications & Management

---

Control panel	LED Status display with on line : on battery
Alarm	Alarm when on battery : distinctive low battery alarm

---

---

## Surge Protection and Filtering

---

Surge energy rate	273 J
-------------------	-------

---

---

## Packing Units

---

Package 1 Weight	4.5 kg
Package 1 Height	22.2 cm
Package 1 Width	14.2 cm
Package 1 Length	34.6 cm
SCC14	10731304417610

---

---

## Offer Sustainability

---

EU RoHS Directive	Under investigation
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

---

---

## Contractual warranty

---

Warranty	2 years repair or replace
----------	---------------------------

---